

DIVA 552



Indiana Line – an italian brand with traditions

Indiana Line has been famous for the production of loudspeakers for nearly 50 years. This Italian brand is distinguished from the competition by the optimized production process and the rational use of components, which results in above-average quality of workmanship and sound.

Let yourself be surprised by the sound smoothness that is difficult to achieve

The 2,5-way Diva 552 floorstanding loudspeaker offers enviable resolution and the naturalness of voice reproduction, with a quick and precise impulse response. The warm and deep bass is complemented by the natural, extremely detailed high frequencies. As for a construction of this size, the loudspeaker offers a unique sound scale.

Nearly 50 years of experience in creating loudspeaker technology

The tweeter with a diameter of 26 mm is attached to the Diva 552 speaker through a soft rubber cover, which significantly reduces vibrations transmitted from the cabinet. It has been equipped with a radial rear chamber that uses two different types of sound damping materials.

The stiff and light cones of the 140 mm mid-woofers are made of Curv material – a woven, extruded polypropylene with high damping. The lower 140 mm diameter woofer has received an air-dried cellulose pulp membrane. The magnetic circuits of both drivers use an aluminum ring to reduce

non-linearities, maximizing resolution also at high volume levels.

Choose the perfect parameters for your interior

The amplifier loading impedance the Diva 552 is 4 – 8 ohms, and the dedicated amplifier power is 30 – 130 W. The loudspeaker is recommended for rooms of up to 20 m², where it will certainly be its decoration.

Be mesmerized by industry-leading design

The Diva 552 loudspeakers are finished in an elegant black high-gloss lacquer and will perfectly complement any interior. The double speaker terminals enable bi-wiring or bi-amping.

The most important features of the Diva 552 model:

- 2,5-way floorstanding acoustical design
- Crossover frequencies: 300 Hz and 2,8 kHz
- 140 mm mid-woofer with Curv cone
- 140 mm bass driver with natural cellulose pulp cone
- 26 mm silk dome tweeter
- Bass reflex cabinet with a port at the front
- Frequency response: 40 Hz to 22 kHz
- Bi-amping / bi-wiring capability
- Black piano lacquer finish
- Suggested amplifier power: 30 – 130 W
- Sensitivity: 90 dB (2,8 V / 1 m)
- Dimensions (H x W x D): 825 x 160 x 240 mm
- Weight: 12,1 kg